

DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011

1. Unique identification code of the product-type:
**Jupiter 470-850 see through insert room heater burning solid fuel without hot water supply DS/
EN 13229:2001/A1:2003/A2: 2004
CEN/TS 15883**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):
Jupiter 470-850 see through insert room heater burning solid fuel without hot water supply
3. Intended use or uses of construction product, in accordance with the applicable harmonized technical specification , as foreseen by the manufacturer:
Room heater burning solid fuel without hot water supply
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):
**Meteor A/S
Drejervej 1, DK-7451 Sunds Tlf: +45 97 14 13 33 – Fax. +45 97 14 14 35 Email: mail@meteor.dk**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):
**Meteor A/S
Drejervej 1, DK-7451 Sunds Tlf: +45 97 14 13 33 – Fax. +45 97 14 14 35 Email: mail@meteor.dk**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
**TEKNOLIGISK INSTITUT DANAK-accredited testing laboratory number 1235
Test Report Number: 300-ELAB-2175 EN**

8. Declared performance

Harmonized technical specification	DS/EN 13229:2001/A1:2003/A2:2004
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials <i>See instruction manual for correct installation.</i> <i>Must only be in connection with non-combustible material</i>	Minimum distances, in mm rear = - sides = 150/350 front = 1100 floor = 300
Risk of burning fuel falling out	Pass
Emission of combustion products	CO: 0,11% Nox:118 mg/Nm ³ Dust: 27 mg/Nm ³ OGC: 81 mg/Nm ³
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T: 242 °C
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	9,1 kW
Room heating output	9,1 kW
Water heating output	- kW
Energy efficiency	76 %

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rene Poulsen (Director).....
(Name and function)

Sunds 01.09.2015.....
(Place and date of issue)



(Signature)