

PRODUCT INFORMATION:

Thermal energy:	71,6 kWh,	PL: 73,7 kWh
Energy efficiency:	85 %,	PL: 88 %
CO%:	0,09 %,	PL: 0,09 %
Heat storage capacity:		
	100 % after 7,6 hours,	PL: after 8,9 hours
	50% after 25,2 hours,	PL: after 29,5 hours
	25% after 42,3 hours,	PL: after 49,6 hours

PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
BLANKA	3T	1790	1824
BLANKA-1	3T-1	1835	1824
BLANKA-2	3T-2	1790	1824
BLANKA PL	3TP	2260	1824
BLANKA G	3TG	1820	1824
BLANKA PL G	3TPG	2295	1824

NEEDED FOR ASSEMBLY:


* Mortar 1 x 25 kg (not included in NunnaUuni delivery).

NOTE!


See the product pictures of PL and glass models (G) from the 3pdf!




BLANKA



BLANKA PL



BLANKA G



BLANKA PL G



BLANKA-1



BLANKA-2

PL = Top connection

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Blanka / Blanka G	-	-	33	20	-	221	-12	17	160	310
Blanka PL / Blanka PL G	-	-	33	20	-	221	-12	17	160	310

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]			FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Blanka / Blanka G	-	x	x	150-180	250	350	370	-	920006	70-100
Blanka PL / Blanka PL G	-	-	-	-	-	-	514	-	920006	70-100

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Blanka / Blanka G	50	200	200	1000
Blanka PL / Blanka PL G	50	200	200	1000

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

Take a notice of the countryspecific approvals in section 3

NOTES!

The flue heat category required by the fireplace is T400.

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

Country- and region-specific regulations must be adhered to when installing the fireplace

